



Design Pressure = 150 PSI @ 120 °F
 Min. Design Temperature = 20 °F @ 150 PSI
 Hydrotest Pressure = 165 PSI

150 PSI
 MEGA
 SIDE PORT



NOTE: STANDARD PARTS ARE SHOWN FOR REFERENCE ONLY
 CHECK ORIGINAL ORDER FOR ORDERING SPARE PARTS

***P1 Not Available With 4" Mega Side Port**

Shell Length Code	L inch (mm)	P3 Standard inch (mm)	*P1 Optional inch (mm)	S Span in (mm)	Empty Weight lb (kg)
-1	56.1 [1425]	46 [1168.40]	47 [1194]	1 @ 28 [711]	69 [31]
-1.5	76.1 [1932.94]	66 [1676.40]	67 [1701.80]	1 @ 42 [1066.80]	76 [34]
-2	96.1 [2440.94]	86 [2184.40]	87 [2209.80]	1 @ 56 [1422.40]	83 [38]
-3	136.1 [3456.94]	126 [3200.40]	127 [3225.80]	1 @ 80 [2032.00]	97 [44]
-4	176.1 [4472.94]	166 [4216.40]	167 [4241.80]	2 @ 64 [1625.60]	111 [50]
-5	216.1 [5488.94]	206 [5232.40]	207 [5257.80]	2 @ 78 [1981.20]	125 [57]
-6	256.1 [6504.94]	246 [6248.40]	247 [6273.80]	2 @ 92 [2336.80]	139 [63]
-7	296.2 [7523.48]	286 [7264.40]	287 [7289.80]	2 @ 106 [2692.40]	153 [69]
-7.5	316.2 [8031.48]	306 [7772.40]	307 [7797.80]	2 @ 114 [2895.60]	160 [73]
-8	336.2 [8539.48]	326 [8280.40]	327 [8305.80]	2 @ 120 [3048.00]	167 [76]

ITEM	QTY	P/N	DESCRIPTION	MATERIAL
1	1	4080409	Shell	Filament Wound, Epoxy FRP
2	2	4080008	Bearing Plate	6061-T6 Aluminum, SB-221, Anodized
3	2	4080177-3	Sealing Plate	Noryl GFN2
4	2	4080254-1	Feed/Concentrate Port, 3", "K"	Stainless Steel, 316, SA-312
5	4	6201343	Retaining Ring, F/C Port, 3", "K"	Stainless Steel, 316, SA-479
6	2	6188504-N	O-Ring Seal, F/C Port, 3", "K"	Ethylene Propylene
7	2	4080309	Permeate Port	Noryl GFN2
8	2	6100442MK	Head Seal	Ethylene Propylene
9	2	6110229-N	Permeate Port Seal	Ethylene Propylene
10	2	4080080	Retaining Ring w/ Finger Pull	Stainless Steel, 316
11	2	6121200	Retaining Ring, Permeate Port	Stainless Steel, 316
12	2*	4080173	Support Saddle	Thermoplastic Rubber
13	2	4080137	Strap Assembly	Stainless Steel, 316
14	4	6150001	Strap Screw	Stainless Steel, 18-8
15	2	A/R	Adapter	Thermoplastic
16	1	4080165-1	Thrust Cone	PVC Thermoplastic
17	2	6110326-N	Adapter Seal	Ethylene Propylene
18	A/R	A/R	PWT Seal	Ethylene Propylene
19	3	4080062-4	Shim, Adapter	Noryl GFN2

*3 each with shell lengths -4 and longer.

NOTES:
 DIMENSIONS IN INCHES (MM APPROX.)
 FOR REFERENCE ONLY, NOT FOR CONSTRUCTION UNLESS CERTIFIED
 SHIMMING OF THE SADDLES MAY BE REQUIRED
 CENTER VESSEL ON 2 OR 3 SUPPORTS AT SPAN(S) "S".
 INCORRECT MANIFOLDING WILL CAUSE SEVERE LOCAL STRESS AROUND PORT AND MAY RESULT IN LEAKS AND PREMATURE FAILURE. TAKE EVERY PRECAUTION LISTED IN THE ENGINEERING PACKET OR USERS MANUAL.
 INTERNAL PERMEATE PRESSURE MUST NOT EXCEED 125 PSI.
 ASME SECTION X, 2010
 RP CODE STAMP OPTIONAL
 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



PRO 8-150-MSP

APPROVED AP 5/10/05	ECO	REVISED 4/28/11	DRAWING 101027	REV L
CHECKED AP 5/10/05				
DRAWN AP 5/10/05	10119			